CAMBO WHERE TRADITION MEETS VISION

ACTUS-XL Camera body

With the introduction of the ACTUS-XL series, Cambo's system is now extended across the Actus line of camera products. Where the Actus Mini excels in being the lightest and smallest camera platform, the ACTUS-XL system is a fusion of both the Actus and Ultima camera platforms, maintaining full camera movements.

Modular is the keyword. The Actus-XL accepts all Actus lens plates and lens adapters, sharing the same mount. On the rear standard you find an easy exchangeable frame holder for either a digital back or a DSLR/Mirrorless camera body.

Both front and rear standard have lateral movements, vertical adjustments, swings as well as tilts, all for optimised control over perspective and selective sharpness.

The default 300mm monorail is suitable for short, medium and long focal length lenses. A separate focus slider and fine focussing racks make it not only quick but very easy and precise to focus.

The compatibility with the Actus Mini platform allows the use of a variety of lens adaptors in combination with several camera bodies. These system bodies are mounted with their bayonets to the upright holder, which can rotate between landscape and portrait position within a second. This can be done without having to remove the camera body or bellows.

When using a digital back, the upright holder will accept any of the Cambo SLW-adapters. For photographers that are using digital backs without Live View, there is an adapter mount available for the Cambo sliding back. There are lens panels available for #0, #1 as well as #3 shutter systems, both mechanical and electronic lenses can be used.



NEW

2016





ACXL-970 digiback frame optional adapter



ACTUS-XL Camera specs:

Overall size length / width / height:	310 x 145 x 340 mm (incl. lenspanel holder and digital back holder) 310 x 145 x 315 mm (incl. lenspanel holder and camera body holder)
Overall weight including mount:	4,8 kg (incl. lenspanelholder and frame holder)
Horizontal lateral movement: Vertical movement: Tilt : Swing : Coarse focussing range: Fine focussing range:	50 mm (25/25) both on front and rear 40 mm (20/20) both on front and rear +20° / -20° both on front and rear +20° / -20° both on front and rear 120 mm (max. extension 160 mm with default rail) 40 mm both front and rear
Available digital back adapters:	SLW-80 Hasselblad-V SLW-89 Hasselblad-H SLW-81 Leaf Afi/Sinar HY6 SLW-83 PhaseOne XF/DF /Mamiya AFd SLW-87 Contax 645
Available system camera bayonets:	AC-780Canon-Eos seriesAC-781Canon-M seriesAC-783Nikon-F seriesAC-785Leica-M seriesAC-786Sony-E seriesAC-787Pentax-K seriesAC-788MicroFourThird camerasAC-789Olympus-OMD seriesAC-790Fuji-X series
Ordering information:	ACTUS-XL-DB Camera Body: 99010982 (incl.bellows and holders) ACTUS-XL-35 Camera Body: 99010984 (incl.bellows and holders)

A choice of additional accessories:

Lens plates:	ACB-0/ACB-1/ACB-3 - ACB-ALP/ACB-WRS	
Lens adapting plates:	ACB-39/ACB-HA/ACB-RZ/ACB-CA/ACB-NF/ACB-LR/ACB-M645/ACB-P645	5
Actar lenses:	ACTAR-24, ACTAR-60	
Bellows WA or Macro:	AC-212/AC-216 - ACBD-252/ACDB-256	
Monorail Extensions:	ULM-15/ULM-25/ULM-42	
Compendium:	AC-343	
Conversion frames:	ACXL-965 for Bayonet / ACXL-970 for digiback	
		2

-for more accessories and more information about accessories see: www.cambo.com

CAMBO Fotografische Industrie BV Haatlanderdijk 45 - P.O.Box 200 NL-8260 AE Kampen The Netherlands Tel : +31(0)38 3314644 Fax : +31(0)38 3315110 Email: info@cambo.com Web : www.cambo.com