

MOUNTING INSTRUCTION FOR UL-35 FUJI S2 KIT

For horizontal (landscape mode) use of the camera you will need to mount the extender part under the Fuji body first, before mounting this combination onto the base mount that is to be mounted on the standard of the Ultima 35. For vertical (portrait mode) use of the camera the extender should be taken off the Fuji and the L-bracket is mounted with the bottom of the Fuji on the left side seen from the rear, so that the cable go out from the top.



Step 1:

Mount the part A into the dovetail mount on the rear standard of the Ultima. Fix it with the allen key with the 3 hexscrews inside the 3 holes, but do not overtighten.



Step 2:


Mount the part B onto the bottom of the Fuji S2 and tighten this firmly. After this, the Fuji with the block can be mounted on top of the Ultima standard which has part A in place. To take the Fuji off, first release the thumbscrew in part A and then remove part B from the Fuji. Part A remains mounted in the Ultima



Using the L-Bracket for vertical mounting:

Step 1:

Mount the L-Bracket onto the mount of part A in the way that the L rises up on the left side seen from the rear. It will locate in place. Tighten well.



Step 2:

Mount the Fuji S2 with the thumbscrew in the L-Bracket so that it aligns in place. It will now be exactly in the optical axis. Cables can be inserted without obstruction.

